



Marking to ATEX 94/9/EC Directive: Ex II 2 G Ex d IIC Gb / II 2 D Ex tb IIIC Db IP66

Zone: 1, 2, 21, 22 , Gas Group IIC

Compliance with: IEC 60079-0 : 2007, IEC 60079-1 : 2007, IEC 60079-31 : 2008

EC Type Examination Certificate: ISSeP 10 ATEX 002U



FEATURES

- Unions are used in electrical conduit installations to enable connections and rotations of pipes, enclosures and equipments independent of each other.
- Made of three pieces in two types of Male/Female and Female/Female.
- Sizes and standard thread available are 1/2" ~ 3" NPT. Other threads supplied on request.
- Material and Finish: Manufactured as standard in galvanized steel. Alternative materials and plating are available on request.



NMUMF Male/Female



NMUFF Female/Female

SIZE REF.	NMUMF1 or NMUFF1	NMUMF2 or NMUFF2	NMUMF3 or NMUFF3	NMUMF4 or NMUFF4	NMUMF5 or NMUFF5	NMUMF6 or NMUFF6	NMUMF7 or NMUFF7
INCH NPT	1/2"	3/4"	1"	1 1/2"	2"	2 1/2"	3"

ORDERING INFORMATION

Specify size reference, thread form and material.

Male or Female entries.

Example: For 1" NPT Female/Female galvanized steel union: NMUFF3 galvanized steel.